



**Key Features**

- 22" TFT LCD Display
- Resolution 1680x1050 @ 60Hz
- Brightness 300cd/m<sup>2</sup>
- Contrast Ratio 1000:1
- Composite Video BNC In / Out, VGA
- Mount - VESA Compatible, 100x100mm
- RGB Analog & DVI-D
- Built-in Speaker
- 3D-Comb, De-Interlace, PIP



**Specifications**

Display Area	22-inch diagonal
Resolution	1680x1050 @ 60Hz
Brightness	300cd/m <sup>2</sup> (typ)
Contrast Ratio	1000:1 (typ)
Video Input Signal	BNC Composite In / Out VGA, S-Video, RGB Analog & DVI-D
Audio Input Signal	RCA Left & Right, Stereo Mini Jack In & Out
Pixel Pitch	0.282 x 0.282mm
Colors	16.7M Colors
Mount	VESA Compatible, 100x100mm
Response Time (Tr+Tf)	5ms
Viewing Angle	±80° (right/left) , 80° (Up) , 80° (Down)
Scanning Frequency	Horizontal 30 ~ 80KHz , Vertical 56 ~ 75Hz
Speaker Power	2 x 2 Watt (Stereo)
Power Voltage	DC Adaptor 12V 3.33A
Power Consumption (Max/DPMS)	<40W/2W
Dimension W x D x H	21.80 x 7.30 18.20 Inch
Weight Net/Gross	14.30 Lb / 18.73 Lb
Regulation Safety	UL, FCC, CE