



**Key Features**

- 24" TFT LCD Display
- Resolution 1920x1200 @ 60Hz
- Brightness 300cd/m<sup>2</sup>
- Contrast Ratio 1000:1
- Composite Video BNC In x 2 / Out x 2, VGA
- Mount - VESA Compatible, 100x100mm
- RGB Analog & DVI-D
- Built-in Speaker
- 3D-Comb, De-Interlace, PIP



**Specifications**

Display Area	24-inch diagonal
Resolution	1920x1200 @ 60Hz
Brightness	300cd/m <sup>2</sup> (typ)
Contrast Ratio	1000:1 (typ)
Video Input Signal	BNC Composite In / Out, VGA, S-Video, RGB Analog & DVI-D
Audio Input Signal	RCA Left & Right
Pixel Pitch	0.270 x 0.270mm
Colors	16.7M Colors
Mount	VESA Compatible, 100x100mm
Response Time (Tr+Tf)	5ms
Viewing Angle	160° / 160°
Scanning Frequency	Horizontal 30 ~ 80KHz , Vertical 56 ~ 75Hz
Speaker Power	3 x 2 Watt (Stereo)
Power Voltage	100 - 240VAC, 60/50Hz
Power Consumption (Max/DPMS)	100W
Dimension W x H x D	23.5"(W) x 17.8"(H) x 8.1"(D) With Stand 23.5"(W) x 17.8"(H) x 3.25"(D) Without Stand
Weight Net/Gross	19.5 Lb / 24.2 Lb
Regulation Safety	FCC, CE